



Characteristics



- Equipped with EC-fans of low consume that save up to 60% of the energy without decreasing the airflow.
- Self-supporting casing construction made of galvanized plated steel, finished in structural epoxy-polyester RAL 9016 as standard. Other colours or stainless steel construction are available on request.
- Low noise centrifugal double inlet fans driven by an external rotor motor with built in thermal protection contact. Provided by five speed selection.
- Micro-perforated inlet grille with filter functions makes unnecessary an intensive filter servicing, only has to be periodically wiped or vacuumed.
- "P" type includes water heated coil. "E" type includes electrical shielded element, three power stages with power switches included. "A" type is without heating, air only.
- Anodised aluminium blow-out vanes, airfoil shaped, adjustable from 0 to 15° each side.
- Control panel and 20m of telephonic cable with fast connectors type RJ45 (Plug & Play), included. Optional: Interface to connect to BMS.

Specifications

Model	Airflow m3/h	Heating Capacity	Water Drop Pressure	Water Connections	Heating Capacity	Water Drop Pressure	Water Connections	Electrical Heating Capacity	Fans Power	Fans Current	Noise Level (5 m)	Weight kg
		80/60°C kW	80/60°C Pa	80/60°C	60/40°C kW	60/40°C Pa	60/40°C	3x400V-50Hz kW	230V-50Hz kW	230V-50Hz A	dB(A)	
WEC 1000 A	2700	-	-	-	-	-	-	-	0,279	1,86	55	38
WEC 1000 P86	2610	12,85	1260	2x3/4"	-	-	-	-	0,279	1,86	55	44
WEC 1000 P64	2610	-	-	-	11,06	6530	2x3/4"	-	0,279	1,86	55	44
WEC 1000 E	2700	-	-	-	-	-	-	3/6/9	0,279	1,86	55	46
WEC 1500 A	3600	-	-	-	-	-	-	-	0,372	2,48	56	55
WEC 1500 P86	3480	18,71	1010	2x3/4"	-	-	-	-	0,372	2,48	56	64
WEC 1500 P64	3480	-	-	-	16,35	9010	2x3/4"	-	0,372	2,48	56	64
WEC 1500 E	3600	-	-	-	-	-	-	4/8/12	0,372	2,48	56	68
WEC 2000 A	5400	-	-	-	-	-	-	-	0,558	3,72	57	72
WEC 2000 P86	5220	28,52	2950	2x3/4"	-	-	-	-	0,558	3,72	57	83
WEC 2000 P64	5220	-	-	-	23,64	7520	2x3/4"	-	0,558	3,72	57	83
WEC 2000 E	5400	-	-	-	-	-	-	6/12/18	0,558	3,72	57	90
WEC 2500 A	6300	-	-	-	-	-	-	-	0,651	4,34	58	76
WEC 2500 P86	6090	35,32	5500	2x3/4"	-	-	-	-	0,651	4,34	58	87
WEC 2500 P64	6090	-	-	-	28,35	5810	2x3/4"	-	0,651	4,34	58	87
WEC 2500 E	6300	-	-	-	-	-	-	6/12/18	0,651	4,34	58	96
WEC 3000 A	7200	-	-	-	-	-	-	-	0,744	4,96	59	86
WEC 3000 P86	6960	42,06	9170	2x3/4"	-	-	-	-	0,744	4,96	59	97
WEC 3000 P64	6960	-	-	-	33,95	9740	2x3/4"	-	0,744	4,96	59	97
WEC 3000 E	7200	-	-	-	-	-	-	8/16/24	0,744	4,96	59	106

Dimensions

