


Dehumidifier

DehuTech 400

Desiccant dehumidifier for drying of air at all conditions, but specially suitable for low temperature and low humidity operation.

Complete self-contained unit including desiccant rotor, fans, filters (EU3), thermistor-type reactivation heater, and controls. Casing in stainless steel.

The unit is ready for connection to standard size duct works, electrical power supply and external humidity sensor.




technical data from

DehuTech

Dehumidifier DehuTech 400

CAPACITY DIAGRAM



EXAMPLE:

Process air: $x_p = 9,0$ g/kg, $t_p = +20^\circ\text{C}$ giving

Dry air: $x_T = 6$ g/kg, $t_T = 20+9,9 = 29,9^\circ\text{C}$

TECHNICAL DATA:

Dehumidification capacity 1,5 kg/h
(at $+20^\circ\text{C}$ and 60% RH.
See capacity diagram for other data)

Dry air flow 400 m³/h
(at 30 Pa available external pressure)


Wet air flow 120 m³/h
(freeblowing)

Power supply 2,3 kW
(1x230 V, 50 Hz)

Weight 23 kg

Max noise level 62,2 dB(A)

DIMENSIONS



Manufacturer:



Enhagsslingan 23, S-18740 TÄBY, Sweden

Phone +46 8 792 04 08 Fax +46 8 792 55 59

E-mail: info@dehutech.com Web site: www.dehutech.com

CONDAIR

TELPU MIKROKLIMATA RISINĀJUMI

Vārnu iela 7 • Rīga • LV-1009 • Latvija
T.+371 28346447 • F.+371 66100122
condair@condair.lv • www.condair.lv